
# SUBMITTAL DATA SHEET

Irrigation & Superbooster Pumps Superbooster | Centrifugal

## **1500XSW Series I Multi-Stage Centrifugal Pumps**

This two stage construction multi-stage centrifugal pump provides pressure to 60 PSI for high pressure applications. Motors are Nema standard construction, coupled shaft design and available in both single and three-phase. Housing and adapter are cast iron. Impeller of your choice - no-lead bronze or plastic.



- Impeller Available in either dynamically balanced no-lead bronze or engineered thermoplastic
- 2 Cast Iron Diffusers Precision machined for greatest efficiency
- 3 Cast Iron Pump Body & Motor Adapter
- 4 Drain Plug

#### 5 - Nema Standard Motor Heavy duty, capacitor start, dual voltage (230/115) with built-in overload protection. Choice of 3/4, 1, 1 1/2, & 2 HP. 60 Hz.

6 - Shaft Seal Standard 3/4" ceramic carbon rotating mechanical seal

#### Performance

| Model    |       | Suction    |      |      | Capacities in GPM at Discharge Pressure |      |      |
|----------|-------|------------|------|------|---|------|------|
| No.      | HP    | Lift - FT. | 20   | 30   | 40                                      | 50   | 60   |
|          |       | 10         | 34.3 | 28.8 | 22.2                                    |      |      |
| 1575XSW  | 3/4   | 15         | 33.2 | 27.6 | 20.4                                    |      |      |
| 1575XSW3 |       | 20         | 32   | 26   | 18.4                                    |      |      |
|          |       | 25         | 29.9 | 24.9 |   |      |      |
|          |       | 10         | 41.7 | 37.7 | 31.7                                    | 24.2 |      |
| 1510XSW  | 1     | 15         | 40   | 36.5 | 30.2                                    | 22.2 |      |
| 1510XSW3 |       | 20         | 36.6 | 34.3 | 28.5                                    | 19.8 |      |
|          |       | 25         | 29.5 | 28.5 | 26.5                                    | 16.5 |      |
|          |       | 10         | 42.3 | 40.5 | 36.5                                    | 32   | 24.5 |
| 1515XSW  | 1 1/2 | 15         | 41.7 | 39.8 | 35.3                                    | 29.3 | 23   |
| 1515XSW3 |       | 20         | 40.3 | 39   | 34                                      | 28   | 21   |
|          |       | 25         | 33.3 | 32.5 | 31                                      | 26.5 | 18.8 |

- To order with plastic impeller, add "P" to model number above. Example: 1575XSWP

#### **Specifications**

| Part No. | Model No. | HP    | Voltage   | Phase | Suction | Discharge | Stages | Ship WT. (lbs.) |
|----------|-----------|-------|-----------|-------|---------|-----------|--------|-----------------|
| 6331-100 | 1575XSW   | 3/4   | 115 / 230 | 1     | 1 1/4"  | 1"        | 2      | 64              |
|          | 1575XSW3  | 3/4   | 230 / 460 | 3     | 1 1/4"  | 1"        | 2      | 59              |
| 6326-100 | 1510XSW   | 1     | 115 / 230 | 1     | 1 1/4"  | 1"        | 2      | 64              |
| 6326-102 | 1510XSW3  | 1     | 230 / 460 | 3     | 1 1/4"  | 1"        | 2      | 61              |
| 6327-100 | 1515XSW   | 1 1/2 | 115 / 230 | 1     | 1 1/4"  | 1"        | 2      | 66              |
| 6327-102 | 1515XSW3  | 1 1/2 | 230 / 460 | 3     | 1 1/4"  | 1"        | 2      | 64              |

- Trouble-free (carbon-ceramic) seal.

### SUBMITTAL INFORMATION

NO-LEAD: The weighted average of the wetted surface of this no-lead product contacted by consumable water contains less than one quarter of one percent (0.25%) lead.



**A.Y. McDonald Mfg. Co.** 4800 Chavenelle Rd Dubuque, IA 52002

**Toll Free:** 1-800-292-2737 sales@aymcdonald.com aymcdonald.com

A.Y. McDonald considers the information on this assembly drawing correct when published. Item and option availability, including specifications, are subject to change without notice.

Submitted by: