



IMPORTANT NOTICE - READ CAREFULLY

Tapered Plug Curb Stops

Installation Instructions

McDonald waterworks products are designed for reliable service. Like all brass products, they can be damaged by improper handling and use.

1. Protect threads. Avoid loose fitting wrenches. Do not drop or impact.
2. Keep the valve clean and free from dirt and debris.
3. Protect valve from freezing, which will distort the key and body of the valve.
4. DO NOT use Vaseline®, plumber's grease, or any other petroleum based product on seals or o-rings.
5. Valve is **not** intended for buried curb box service installations.
6. If the cap is perpendicular to the water line, the valve is closed. If the valve is closed, turn the cap counter-clockwise to open it and if the valve is open, turn the cap clockwise to close it (unless ordered otherwise).
7. Insert stiffeners must be used with all plastic tube except PVC.
8. 1 1/4", 1 1/2" and 2" plug valves are not recommended for use with flexible plastic tubing.
9. Tapered plug valves are not designed for frequent operation (ball valves are recommended for frequent operation).
10. If valve leaks, open and close several times. This may reseal the key properly and stop the leak.
11. DO NOT TIGHTEN NUT AT BOTTOM OF VALVE. Adjusting this nut voids manufacturer's warranty.
12. Use only on cold water services.

Damage caused by improper use and/or handling will void our warranty



IMPORTANT NOTICE - READ CAREFULLY

Tapered Plug Curb Stops

Installation Instructions

McDonald waterworks products are designed for reliable service. Like all brass products, they can be damaged by improper handling and use.

1. Protect threads. Avoid loose fitting wrenches. Do not drop or impact.
2. Keep the valve clean and free from dirt and debris.
3. Protect valve from freezing, which will distort the key and body of the valve.
4. DO NOT use Vaseline®, plumber's grease, or any other petroleum based product on seals or o-rings.
5. Valve is **not** intended for buried curb box service installations.
6. If the cap is perpendicular to the water line, the valve is closed. If the valve is closed, turn the cap counter-clockwise to open it and if the valve is open, turn the cap clockwise to close it (unless ordered otherwise).
7. Insert stiffeners must be used with all plastic tube except PVC.
8. 1 1/4", 1 1/2" and 2" plug valves are not recommended for use with flexible plastic tubing.
9. Tapered plug valves are not designed for frequent operation (ball valves are recommended for frequent operation).
10. If valve leaks, open and close several times. This may reseal the key properly and stop the leak.
11. DO NOT TIGHTEN NUT AT BOTTOM OF VALVE. Adjusting this nut voids manufacturer's warranty.
12. Use only on cold water services.

Damage caused by improper use and/or handling will void our warranty



IMPORTANT NOTICE - READ CAREFULLY

Tapered Plug Curb Stops

Installation Instructions

McDonald waterworks products are designed for reliable service. Like all brass products, they can be damaged by improper handling and use.

1. Protect threads. Avoid loose fitting wrenches. Do not drop or impact.
2. Keep the valve clean and free from dirt and debris.
3. Protect valve from freezing, which will distort the key and body of the valve.
4. DO NOT use Vaseline®, plumber's grease, or any other petroleum based product on seals or o-rings.
5. Valve is **not** intended for buried curb box service installations.
6. If the cap is perpendicular to the water line, the valve is closed. If the valve is closed, turn the cap counter-clockwise to open it and if the valve is open, turn the cap clockwise to close it (unless ordered otherwise).
7. Insert stiffeners must be used with all plastic tube except PVC.
8. 1 1/4", 1 1/2" and 2" plug valves are not recommended for use with flexible plastic tubing.
9. Tapered plug valves are not designed for frequent operation (ball valves are recommended for frequent operation).
10. If valve leaks, open and close several times. This may reseal the key properly and stop the leak.
11. DO NOT TIGHTEN NUT AT BOTTOM OF VALVE. Adjusting this nut voids manufacturer's warranty.
12. Use only on cold water services.

Damage caused by improper use and/or handling will void our warranty



IMPORTANT NOTICE - READ CAREFULLY

Tapered Plug Curb Stops

Installation Instructions

McDonald waterworks products are designed for reliable service. Like all brass products, they can be damaged by improper handling and use.

1. Protect threads. Avoid loose fitting wrenches. Do not drop or impact.
2. Keep the valve clean and free from dirt and debris.
3. Protect valve from freezing, which will distort the key and body of the valve.
4. DO NOT use Vaseline®, plumber's grease, or any other petroleum based product on seals or o-rings.
5. Valve is **not** intended for buried curb box service installations.
6. If the cap is perpendicular to the water line, the valve is closed. If the valve is closed, turn the cap counter-clockwise to open it and if the valve is open, turn the cap clockwise to close it (unless ordered otherwise).
7. Insert stiffeners must be used with all plastic tube except PVC.
8. 1 1/4", 1 1/2" and 2" plug valves are not recommended for use with flexible plastic tubing.
9. Tapered plug valves are not designed for frequent operation (ball valves are recommended for frequent operation).
10. If valve leaks, open and close several times. This may reseal the key properly and stop the leak.
11. DO NOT TIGHTEN NUT AT BOTTOM OF VALVE. Adjusting this nut voids manufacturer's warranty.
12. Use only on cold water services.

Damage caused by improper use and/or handling will void our warranty



IMPORTANT NOTICE - READ CAREFULLY
Tapered Plug Curb Stops

Installation Instructions



WARNING: It is unlawful in **CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014)** to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380.



IMPORTANT NOTICE - READ CAREFULLY
Tapered Plug Curb Stops

Installation Instructions



WARNING: It is unlawful in **CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014)** to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380.



IMPORTANT NOTICE - READ CAREFULLY
Tapered Plug Curb Stops

Installation Instructions



WARNING: It is unlawful in **CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014)** to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380.



IMPORTANT NOTICE - READ CAREFULLY
Tapered Plug Curb Stops

Installation Instructions



WARNING: It is unlawful in **CALIFORNIA & VERMONT (effective 1/1/2010); MARYLAND (effective 1/1/2012); LOUISIANA (effective 1/1/2013) and the UNITED STATES OF AMERICA (effective 1/4/2014)** to use any product in the installation or repair of any public water system or any plumbing in a facility or system that provides water for human consumption if the wetted surface area of the product has a weighted average lead content greater than 0.25%. This prohibition does not extend to service saddles used in California, Louisiana or under USA Public Law 111-380.